



Overview

Our new digital lectern is designed to accommodate a variety of presenters. Its 150mm actuator driven electric height adjustment capabilities offer comfort during seated or standing presentations.

For those with multiple devices, the built-in simple laptop interface allows users to connect easily and switch between presenting material from your dedicated computer and other devices.

The system includes an Integrated Full-HD 22" capacitive dual-touch interactive tablet monitor, which offers ample writing space and high accuracy while entering annotations and presentation highlights.

This sleek and affordable presentation control solution is a cost-effective quality stand-alone addition to your auditorium, theatre or venue.

Features

- Easy notebook cable interface
- Integrated I/O panel
- Front storage compartment
- Wired gooseneck microphone
- Sleek easy-clean finish
- Raises to standing presenter, lowers for seated.

Product highlights

- 22" Interactive tablet monitor
- Electric height-adjustable
- Compatible with all operating systems
- Dual-touch interactive wide angle display

LCD

| | |
|------------------|------------------------------|
| Resolution | 1920 x 1080 (Full HD) |
| View area | 477(H) x 268(V) mm - 22 inch |
| Luminance, white | 250 cd/m ² |
| Contrast ratio | 1000:1(typ) |
| Viewing angle | 160° (H/V) |
| Lamp life time | 20,000 hrs (min) |
| Colour | 8bit, 16.7 million colours |

Tablet

| | |
|----------------------|---------------------------|
| Technology | Electromagnetic resonance |
| Detectable height | 3~10mm |
| Position report rate | 138pps |
| Pressure resolution | 1024 level |

Body

| | |
|---|--|
| Sliding cover | Opening/closing the cover easily |
| Soft wheels | Moving podium with convenience |
| Adjusting monitor angle system actuator | User can set monitor angle as users want |
| Dimension | 790mm (W) x 976mm (H) x 572mm (D) |

Multimedia Controller

| | |
|-----------------|----------------------|
| VGA inputs | VGA x 2 |
| VGA outputs | VGA x 2 |
| Signal type | VGA, SVGA, XGA, QXGA |
| Max resolution | 2048 x 1536 |
| Pixel frequency | 440MHz |

Video

| | |
|-------------------|-------------|
| Composite inputs | Video x 1 |
| Composite outputs | Video x 1 |
| Bandwidth | 100MHz |
| Return loss | -30dB, 5MHz |

Control

| | |
|--------------------------|-----|
| Body UP & DOWN switch | x 1 |
| Monitor UP & DOWN switch | x 1 |

Amplifier

| | |
|--------------------|-------------------------------|
| Output power (max) | 280W 4Ω (140W + 140W) Stereo |
| Microphone inputs | 8~20mV (3 inputs) |
| PC/laptop inputs | 70mV (2 inputs) |
| Audio inputs | 70mV (2 inputs) |
| Audio outputs | 250mV (3 outputs) |
| Frequency response | 25Hz ~ 20KHz |

Other

| | |
|---------------|--------------|
| Power adaptor | 220V 50~60Hz |
|---------------|--------------|

Gooseneck Microphone

| | |
|-------------------------------|------------------|
| Polar pattern | Cardioid |
| Frequency response | 150Hz ~ 17KHz |
| Sensitivity (dB=1V/1Pa, 1KHz) | -46dB |
| Output impedance | 200 ohm balanced |
| Weight | 200g |

Laptop Interface Modules

| | |
|------------|------|
| VGA | x 1 |
| Tablet USB | x 1 |
| USB | x 21 |
| Sound in | x 1 |
| Sound out | x 1 |
| Power | x 1 |

What's in the box

| | |
|--------------------|-----|
| Mouse pad | x 1 |
| Stylus / EMR touch | x 1 |
| AC cable / 1.5M | x 1 |
| Stand MIC cover | x 1 |
| Speaker | x 1 |

Distributed by: