





Overview

The AV controller, also referred to as the integrator, can be used with your choice of speakers. It uses digital audio amplifier circuitry to produce clear and crisp sound replicated at full efficiency with no loss in sound quality. This panel is the 'brain' that controls the entire system.

With its in-built microphone function as well as its separate volume control, it means this integrator is fully flexible allowing users to mix sound inputs. The system is also extendable and if needed can be connected to additional amplifier via its variable audio line output located at the back. This means users are not just restricted to the in-built amplifier alone.

The MP3, input further extends the flexibility of this integrator allowing users the option to add music via the standard 3.5mm cable. Additionally, the HDMI, USB and VGA input in the front panel enhances the user-friendliness of the system.



Features

- A true all-in-one integrated speaker system specially
- designed to work with your HDI series of products
- The panel provides all of the connections you will ever need, including:
 - Two volume controls (Master and Microphone)
 - Access to MP3, USB, HDMI,VGA and a microphone jack
 - An in-built audio codec that will take the audio signal from your PC to the USB cable
 - -An in-built digital amplifier
 - A mute button
- The system also comes with two streamlined 25W speakers tuned for voice reproduction
- Output from the panel include: USB, HDMI, Variable Line
- OUT and VGA
- Easy to install with step-by-step instructions





Integrated Ceiling Speaker System

$\overline{}$			
G	\sim \sim	\circ r	\sim
		-1	a
<u> </u>	U 1	U	u

Frequency response 20Hz~20KHz SNR 80dB

Power output 2 x 25W (8 Ohms) @ THD = 10%

Power supply DC 24V

Case dimension 155mm (W) x 110mm (D) x 90mm (H)

Stereo channel seperation 60 dB

CMRR >70dB @ 20Hz~20KHz

THD + Noise ≤3%
Power consumption 6W
Product weight 0.5kg

Product warranty 12 month back to base

Audio Input

MP3 1 x Stereo audio 3.5mm jack

MIC 1 x 6.5mm jack

AUX 1 x Stereo audio 3.5mm jack

Input impedance >10kΩ

Audio Output

 Speaker
 1 x Phoenix connector

 Variable line out
 1 x Stereo audio 3.5mm jack

 Output impedance
 50Ω / stereo, 8Ω / amplifier

Video Input

VGA 1 x 15mm female VGA
HDMI 19pin female HDMI

Video Output

VGA 1 x 15mm female VGA HDMI 19pin female HDMI

Computer Input

USB 1 x USB type B

Computer Output

USB 1 x USB type A USB THRU 1 x USB type A

What's in the box

Audio controller / x 1 amplifier x 2 Speaker Speaker bracket - to x 2 attach to IWB Speaker bracket - to x 2 attach to wall x 2 Speaker cable USB cable (A-B type) x 1 Power cable x 1 User manual x 1 Power supply x 1 Wall plug x 4 Screw to suit wall plug x 4 Screw (black) to attach x 4 bracket to speaker Screw to mount speaker x 4 bracket to IWB

