



Totally Integrated,  
**Collaborative & Interactive**  
 Touch Hub for the **360**  
 experience.



### 4K Capacitive touch screen

4K resolution provides an ideal medium for presentations. PCAP technology **optically bonded**



### Android

5.1 (Lollipop) OS Version  
 Quad Core 1.2GHz CPU  
 2G DRAM.



### Camera (optional)

4K Ultra HD video calling  
 Super-wide 120-degree field of view  
 and integrated audio.



### HDI Connect

Available to display any device in the room. Simple one button press for wireless presentations.



### Easy Connectivity

Various inputs including USB (touch and memory), HDMI from the side and RS232.



### Easy Pen

Walk up + use whiteboarding.



### Side Speaker bar

For better sound experience with 2 x 20W speakers.




### OPS PC

Integrated Windows 10 available.



### Edge to Edge design

True flat touch screen for elegant design.



### No air gap

No gap between your finger and cursor and quicker response



### Drive the 360 like you would your smartphone

By touching your home button, you can directly access the Android home page for complete ease of use.



### Compatible

Compatible with Android and Mac.

# HDI PCAP 360™

## LED PANEL

Diagonal size	84"(213.50 cm)
Display Resolution (Max.)	3840 X 2160 (QWUXGA)
Brightness (average)	350 cd/m
Viewing Angle	H: 178° / V: 178° (CR>=10)
Contrast ratio	1400:1(Typ.)
Supported Colors	1.06 B colors (10bit(D))
Response Time	5 ms (GTG)
Display Frame Rate	120Hz
Installation	Landscape Orientation

## CONNECTIVITY

Front	-
Side	USB A x 2, USB B x 1, HDMI x 1 "HDMI x 3, UHD DP x 1, PC
Rear	RGB, Audio-In/Out, USB3.0 x 1, USB2.0 x 1, USB B x 1 , Speaker Out (R/L), Line out, RS-232C (D-sub 9-pin), RJ45"

## MECHANICAL

Dimensions Landscape	2143 X 1190 X 110 mm
Weight	114kg (251 lbs)
VESA mount	600 x 400 (mm), M8 Screw
Front Glass	Tempered Glass 4.0t (Anti-glare Type)
Cooling	Fanless

## ENVIRONMENTAL

Operating Temperature	0 ~ 40 °C (32 ~104°F)
Storage Temperature	- 20 ~ 60 °C (-4 ~ 140 °F)
Operating Humidity	20% to 80% RH (no condensation)

## ACCESSORIES

PCAP Pen x 1, Remote controller, HDMI Cable 3m, USB Cable (A-B) 3m, Power Cable, User Manual (CD)

## TOUCH

Detect area	1860.48(H) x 1046.52(V) mm / 73.24"(H) x 41.20"(V)
Detection method	Optically Bonded Capacitive Touch Sensor
Touch tool	Stylus Pen or Hands
Accuracy	±2mm
Response time	< 10ms
Available Touch Point	PCAP : 60 Points
Operating Systems	Window 7, 8, 10 / MAC 10.10 ~ 10.11 Android 5.1
PC connector	USB

## ANDROID

System version	Android 5.1
CPU	1.2GHz. Quad Core. 64bit
GPU	Hexa Core
RAM	2GB(DDR3)
FLASH	8GB

## ELECTRIC

Power Requirement	100 - 240V AC, 50/60 (Hz)
Power Consumption	Max. 430W
Power Consump. (Standby)	< 0.5W
Speaker Output	20W + 20W Stereo (8-ohms)

## OSD

OSD Control	RS232C, IR Remote controller, Touch
OSD Language	English / Français / Deutsch / Spanish / Dutch / Russian / Korean / Japanese / Chinese
OSD Key Lock	Support
Regulatory approvals	CB, CE, FCC, NRTL, RoHS, PSE, RCM

## OPTIONS

OPS PC(AOPS-7080), Wall-mount(AB-900)

Totally Integrated,  
**Collaborative & Interactive**  
Touch Hub for the **360**  
experience.