

# HDI-65 EDGE

**HDI** edge  
NEW GENERATION

## 65" Multi-touch Screen Slim IR

HDI Edge multi touch screens incorporate 20 points of touch with the slimmest IR screen on the market.

Complete with Android 8.0, the system is completely plug and play, with no drivers necessary for interaction.

All HDi screens work with Windows, OSX and Linux operating systems.

The screen's 4K resolution, LED high brightness backlight and wide screen format provides an ideal medium for presentation, interaction and collaboration.

There are ample I/O ports that would suit any audio-visual environment, making the HDi Edge a must-have companion for education, government and the corporate sector.

HDI Edge multi touch screens come ready for easy wall or trolley installation.

**4K** 4K resolution

**Slim IR**  
technology

**4 mm**  
toughened glass

**Mobility**  
Options



## Features

- Optical Slim IR Technology
- 4K resolution (3840 x 2160 px)
- Powered by HDi OS™ (Built on Android 8.0)
- Multi-touch – Up to 20 touch points
- Pre-installed interactive apps
- Integrated inbuilt sound bar
- Integrated OPS Slot (OPS units sold separately)
- HDi Sketch™ app
- USB-C front socket
- Mobile and electric height-adjustable options available
- 5 Year on-site warranty
- Ships with wall-mount bracket



**HDI** edge  
NEW GENERATION

## TECHNICAL SPECIFICATIONS

Resolution	Up to 3840 x 2160 @ 60Hz
Display Features	LED backlight
Screen dimension	65" / 1640mm
Set dimension	57.83" (L) x 36.04" (H) x 3.66" (W) / 1469.1mm (L) x 915.6mm (H) x 93.2mm (W) - Not including base
Temperature / Humidity	0°C ~ 40° / ≤80%
Net weight	36KG / 79.36lb
Aspect Ratio	16:9
Brightness	400cd/m2
Contrast	1300:1
Colours	10bit, 1.07 Billion colours
View Angle	178°
Screen Mode	16:9 / 4:3 / Point to point
Video Mode	PAL, NTSC, SECAM
Sound Mode	D/K, B/G, I, M
Support Resolution	1280x960 / 1280x1024 / 1360x768 / 1440x900 / 1600x1200 / 1920x1080 / 3840 x 2160@60Hz
Voltage range	AC 100-240V~, 50/60Hz
Power range	Standby Power <1W - Working 250W
Audio	15W x 15W internal speakers
VESA mount	400 x 300 mm, M8 Screw
Computer compatibility	VGA / SVGA / XGA / SXGA / UXGA

## INPUTS

CVBS/Audio input	1 x MINI (black)
YPbPr	1 x MINI (black)
SD Card	1 x SD Card
Network	1 x RJ45 / Control LAN
USB input	Front: 1 x USB2.0 (Multi use both Android and PC) , 1xPC (Multi use both Android and PC), 1 x Media (Multi use both Android and PC), 1 x Type C (Support USB, Audio & Video) Rear: 1 x USB3.0 USB-A, 1xUSB2.0
PC RGB input	1 x D-USB 15pin
PC audio input	1 x 3.5 stereo audio-in jack
HDMI input	3 x HDMI-A, one in front
HDMI format	2 x HDMI 2.0 (back), 1 x HDMI 1.4 (front, Max support FHD@60Hz)
Interactive control input	2 x USB-B, one in front
USB file system	FAT32, FAT16, NTFS (NTFS compressed file is not supported)
DP	Display Port Input 1.2
RS-232	9 PIN D-SUB

## OUTPUTS

CVBS/Audio out	1 x MINI (Black)
Headphone	1 x Earphone Jack
SPDIF output	1 x RCA
HDMI	1 x HDMI-A Rear
Touch	Pass through touch

## ANDROID 8.0 SPECIFICATIONS

CPU	2*ARM Cortex-A73 1.5GHz 2*ARM Cortex-A53 1.5GHz
GPU	ARM Mali-G51 450 MHz
Flash	32GB Build in EMMC
SDRAM	4GB DDR4
Android Version	8.0
SD Card	Support MAX 32GB SD Card
WIFI	IEEE802.11 a/b/g/n 2.4 GHz + 5.0GHz

## TOUCH PARAMETERS

Touch points	Up to 20 point multi touch
Writing mode	Finger, stylus or any non-transparent object
Positioning technology	IR technology
Positioning accuracy	+2mm
Positioning resolution	4096 x 4096
Writing response time	First point < 8ms, consecutive < 4ms
Cursor speed	>180 dot/sec
Interactive touch control	USB plug and play
Operating system	Windows / Linux / Mac / Android
PC response	System auto response

## SCREEN PACKAGE

Dimensions	64.17" (L) x 41.73" (H) x 8.26" (W) / 1630mm (L) x 1060mm (H) x 210mm (W)
Gross weight	49KG / 108.02lb

### Remark:

Above mentioned parameters are for Standard models and are subject to change without notice. \* Not all applications are compatible with Android 8.0.



## MOBILITY Solutions

At HDi we pride ourselves on designing and building customised solutions to solve many bespoke problems.

