HDi edge 2.0 touch screen 65"



Code: HDi-65 EDGE 2.0

HDi Edge multi touch screens incorporate 20 points of touch with the slimmest IR screen on the market.

Complete with HDi OS Android, the system is completely plug and play, with no drivers necessary for interaction. All HDi screens work with Windows, OSX and Linux operating systems.

The screens 4K resolution, LED high brightness backlight and wide screen format provides an ideal medium for presentation, interaction and collaboration.

HDi Edge multi touch screens come ready for easy wall or trolley installation.



HDi edge



Features

- Optical Slim IR Technology
- 4K resolution (3840 x 2160 px)
- Powered by HDi OS™ (Built on Android 11)
- Multi-touch Up to 20 touch points
- Inbuilt Airserver app for device mirroring
- Pre-installed interactive apps
- 2 x 15w front facing speakers
- Integrated Mini OPS Slot (Mini OPS units sold separately)
- USB-C front socket
- Mobile and electric height-adjustable options available
- 5 Year on-site warranty
- Ships with wall-mount bracket



HDi edge 2.0 touch screen 65"

TECHNICAL SPECIFICATIONS

| Resolution | Up to 3840 x 2160 @ 60Hz | |
|------------------------|--|--|
| Display Features | LED backlight | |
| Screen dimension | 65" / 1640mm | |
| Set dimension | 58.14" (L) x 36.13" (H) x 3.45" (W) / 1476.8mm (L) x 917.8mm (H) x 87.7mm (W) - Not including base | |
| Temperature / Humidity | 0°C ~ 40° / ≤80% | |
| Net weight | 36KG / 79.36lbs | |
| Aspect Ratio | 16:9 | |
| Brightness | 350 cd/m2 | |
| Contrast | 1200:1 or higher | |
| Colours | 10bit, 1.07 Billion colours | |
| View Angle | 178° | |
| Screen Mode | 16:9 / 4:3 / dot to dot / Full screen | |
| Support Resolution | 4K Ultra HD 3840 x 2160 @60Hz | |
| Voltage range | AC 100-240V~, 50/60Hz | |
| Power range | Standby Power <1W - Working 230W | |
| Audio | 15W x 15W internal speakers | |
| VESA mount | 400 x 300 mm, M8 Screw | |
| Panel Response Time | 8 ms | |

CONNECTIVITY

| FRONT | | REAR |
|------------------|-------------|------------------|
| HDMI | 1 | SIDE |
| USB 3.0 A (Blue) | 3 | HDMI |
| USB 3.0 B (Blue) | 1 x (Touch) | USB 2. |
| USB 3.0 Type C | 1 | USB 2. USB 3. |
| | | 0303. |

| REAR | | |
|-------------------|------------|--|
| SIDE | | |
| HDMI | 2 | |
| USB 2.0 A (White) | 1 | |
| USB 3.0 A (Blue) | 2 | |
| USB 3.0 B (Touch) | 1 | |
| USB 3.0 Type C | 1 | |
| DP | 1 | |
| HDMI OUT | 1 | |
| DOTTOM | | |
| BOTTOM | | |
| VGA | 1 x DE-15F | |

| VGA | |
|----------------------|--|
| VGA Audio (PC) Input | |
| MIC Input | |
| Headphone Out | |
| Network (LAN) | |
| USB 3.0 B (Touch) | |
| SPDIF | |
| | |

1 x 3.5 stereo 1 x 3.5 stereo 1 x 3.5 2 x RJ45 IN - OUT 1 1 RCA

ANDROID 11 SPECIFICATIONS

| CPU | 4 x ARM Cortex-A73 2.28GHz 64 bits |
|----------------|------------------------------------|
| CPU | 4 x ARM Cortex-A53 2.28GHz 64 bits |
| GPU | 8 x ARM Mali-G52 |
| Dual wifi card | WIFI 6 & 8 Bluetooth + WIFI 5G |
| SD RAM | 8GB DDR4 |
| EMMC | 64G |

TOUCH PARAMETERS

| Touch Technology | Infared Touch |
|------------------------|--|
| Touch points | Up to 20 point multi touch |
| Writing mode | Finger, stylus or any non-transparent object |
| Positioning technology | IR technology |
| Positioning accuracy | <1mm |
| Positioning resolution | 4096 x 4096 |
| Response time | 5ms |
| Cursor speed | 180 dot/sec |
| Connection Port | USB plug and play |
| Operating system | Windows / Linux / Mac / Android |
| PC response | System auto response |
| | |



HD

MOBILITY Solutions

At HDi we pride ourselves on designing and building customised solutions to solve many bespoke problems.

PHYSICAL SPECIFICATIONS 64.80" (L) x 42.28" (H) x 8.86" (W) Package Dimensions

| r achage principione | 1646mm (L) x 1074mm (H) x 225mm (W) |
|----------------------|---|
| Gross weight in box | 50KG / 110.23lbs |
| Screen Dimensions | 1476.8mm (L) x 917.8mm (H) x 87.7mm (W) |
| Net Weight | 36KG / 79.36lbs |

Remark:

Above mentioned parameters are for Standard models and are subject to change without notice. * Not all applications are compatible with Android 11.



/