

HDi Display 65"

HDi display

Code: HDI-55 Display

HDi introduces its new 4K LCD HDi Non-interactive display designed to offer great performance in any application. Featuring a slim bezel design, it is an ideal display for any corporate or education environment.

The new HDi Display includes multiple connectivity options and features 350 cd/m2 brightness. It also comes with 4mm toughened glass that makes it resistant to any rough environment.

The HDi Display comes with a 3 Year warranty supported by our professional support team.



4K resolution



Toughened glass



178 Viewing Angle



16.7 million colours

Features

- 4K resolution (3840 x 2160 px)
- Non- interactive display for wall-mount or stand
- Toughened glass
- Brightness 350 cd/m2
- Contrast 4000:1
- Viewing Angle 178°
- 16.7M Colours
- 4 mm toughened glass
- Mobile and electric height-adjustable options available
- 3 Year on-site warranty

HDi Display 65"

TECHNICAL SPECIFICATIONS

Resolution	Up to 3840 x 2160 @60Hz
Display Features	DLED
Screen dimension	65"
Display area	1428.5 (H) x 803.5 (V) mm (64.53 inch)
Dimensions	1252.3 (H) x 728.9 (V) x 83.9 (D) mm
Temperature / Humidity	0°C ~ 40° / 20°C ~ 60°C /10% - 90% No condensation
Weight	35kg
Aspect Ratio	16:9
Frequency	60Hz
Brightness	350 cd/m2 (max)
Contrast	4000:1
Colours	16.7 M
View Angle	H 178° , V 178°
Life time (typ)/(min)	50000h
Voltage range	Rating 100- 240V~, v-50/60Hz
Power range	Stand by Power <0.5W - Max power: 250W
Speaker	2 x 10W (8Ω) THD+N<10%@1KHz
VESA mount	400mm x 200mm

I/O PORTS

HDMI IN	1
USB 2.0 IN	1
USB 2.0	1
RS232	1

SCREEN PACKAGE

Dimensions	1590 (H), 200 (V), 1000 (D)mm
Gross weight	40kg

INSIDE THE BOX

Remote controller	1
Power cable	1



MOBILITY solutions

At HDi we pride ourselves on designing and building customised solutions to solve many bespoke problems.

Remark:

Above mentioned parameters are for Standard models and are subject to change without notice.