HDi Display 75"



Code: HDI-75 Display

HDi introduces its new 4K LCD HDi Non-interactive display designed to offer great performance in any application. Featuring a slim bezel design, it is an ideal display for any corporate or education environment.

The new HDi Display includes multiple connectivity options and features 350 cd/m2 brightness. It also comes with 4mm toughened glass that makes it resistant to any rough environment.

The HDi Display comes with a 3 Year warranty supported by our professional support team.





4K resolution



Toughened glass



178 Viewing Angle



16.7 million colours

Features

- 4K resolution (3840 x 2160 px)
- Non- interactive display for wall-mount or stand
- Toughened glass
- Brightness 350 cd/m2
- Contrast 4000:1
- Viewing Angle 178°
- 16.7M Colours
- 4 mm toughened glass
- Mobile and electric height-adjustable options available
- 3 Year on-site warranty

HDi Display 75"

TECHNICAL SPECIFICATIONS

Resolution Up to 3840 x 2160 @60Hz

Display Features DLED

Screen dimension 75"

Display area 1650.3 (H) x 928.3 (V) mm(74.54 inch)
Dimensions 1710.6 (H) x 990 (V) x 99.4 (D) mm

Temperature / Humidity 0°C ~ 40° / 10% - 90% No condensation

Weight 42kg Aspect Ratio 16:9 Frequency 60Hz

Brightness 350 cd/m2 (max)
Contrast 4000:1

Colours 16.7 M
View Angle 178°
Life time (typ)/(min) 50000h

Voltage range Rating 100- 240V~, v-50/60Hz

Power range Stand by Power < 0.5W - Max power: 350W

Speaker 2 x 10W internal rear facing speakers, THD+N<10% @1KHz

VESA mount 600 x 500mm

I/O PORTS

HDMI IN 1
USB 2.0 IN 1
USB 2.0 1
RS232 1

SCREEN PACKAGE

Dimensions 1590 (H), 200 (V), 1000 (D)mm

Gross weight 47kg

INSIDE THE BOX

Remote controller 1
Power cable 1



MOBILITY solutions

At HDi we pride ourselves on designing and building customised solutions to solve many bespoke problems.

Remark

Above mentioned parameters are for Standard models and are subject to change without notice.

