HDi Flex touchscreen 55"

Code: HDI-55 Flex



HDi Flex is Australia's brightest and most secure interactive touchscreen, boasting 4K resolution, 20 points of touch, and toughened glass for unparalleled durability in any environment. With a unique 500 nits brightness, the Flex stands out as one of the few touchscreens on the market considered 'sunlight readable'.

For security-conscious users, the HDi Flex offers the most secure solution with no Android operating system embedded ensuring the Flex is driven by a computer of your choice.



Exceptional Brightness



Ultra-Secure Screen



4K Resolution



4 mm Toughened glass



Features

- 500 nits brightness
- No onboard Android operating system
- 4K native resolution (3840 x 2160 px)
- Integrated Mini OPS Slot (Mini OPS units sold separately)
- 4mm toughened glass
- Multi-touch Up to 20 touch points
- 5 years warranty
- Available in 55", 65", 75", 86", 98" and 110"
- Australian made mobile and electric height-adjustable options available

What is in the box?

- 1 x Magnetic Pen
- 1 x HDMI Cable
- 1 x Touch USB
- 1x Power IEC Cable
- 1x Warranty Card
- 1 x Remote

HDi Flex touchscreen 55"

TECHNICAL SPECIFICATIONS

Resolution Up to 3840 x 2160 @ 60Hz

Display Features Direct LED

Screen dimension 55" (1209.6mm x 680.4mm)

Set dimension 1274mm (W) x 738.9mm (H) x 79.5mm (D)

Temperature $0^{\circ}\text{C} \sim 40^{\circ}$ Net weight30KgsAspect Ratio16:9Brightness 500 cd/m^2 Contrast1200:1 or higher

Colours 8bit + FRC, 1.07 Billion colours

View Angle 178°

Support Resolution 4K Ultra HD 3840 x 2160 @60Hz Voltage range AC 100-240V~, 50/60Hz

 $\begin{array}{lll} \text{Audio} & 15\text{W} \times 2/8\Omega \\ \text{VESA mount} & 400\text{mm} \times 400\text{mm} \\ \text{Installation} & \text{Landscape/Portrait} \end{array}$

CONNECTIVITY

REAR	
HDMI 2.0	2 (HDMI1 Support HDMI CEC, ARC)
AV IN	1
USB 2.0	1 (Support media and upgrade)
USB 3.0	3 (only support OPS, HDMI 1/2)
Touch USB	2
TYPE -C	1 (Support USB/touch/image/video 4K@60Hz/fast charging 20V, MAX 65W)
Earphone Output	1
RS232	1
OPS Slot	1

TOUCH PARAMETERS

Touch Technology	Infared Touch
Touch points	20 Touch Points
Writing mode	Finger or stylus
Touch accuracy	< 2mm
Cursor Speed	>180 dot/s
Response time	<8ms
Connection Port	USB-B

COVER GLASS

Thickness	4mm
Hardness	7H

PHYSICAL SPECIFICATIONS

Package Dimensions	1400mm (W) x 870mm (H) x 200mm (D)		
Gross weight in box	40Kgs		
Screen Dimensions	1274mm (W) x 738.9mm (H) x 79.5mm (D)		
Net Weight	30Kgs		

RECOMMENDED ACCESSORIES

- Windows OPS
- Android OPS
- HDMI Touch Port Extender
- AirServer Connect 2
- AirServer Connect 3



MOBILITY

Solutions

At HDi we pride ourselves on designing and building customised solutions to solve many bespoke problems.

Remark:

Above mentioned parameters are for Standard models and are subject to change without notice.



