

# HDi edge 2.0 touchscreen 55"



Code: HDI-55 EDGE 2.0


HDi edge 2.0 interactive touchscreens build upon HDi's renowned interactive technology to give the ultimate medium for presentations, interaction and collaboration.

Every HDi Edge 2.0 interactive screen incorporates 20 points of touch, dual Wi-Fi for improved Airserver screen sharing, USB-C ports for single cable connectivity, remote management and access to both the Google Play Store and HDi's own managed app store.

With 4K resolution and a 16:9 wide screen format, the HDi edge 2.0 screen is perfect for any viewing area.



4K Resolution



AirServer App



4 mm  
Toughened glass



Slim IR  
Technology



## Features

- Optical Slim IR Technology
- 4K resolution (3840 x 2160 px)
- Powered by HDi OS™ (Built on Android 13)
- Multi-touch – Up to 20 touch points
- Inbuilt Airserver app for device mirroring
- Pre-installed interactive apps
- 2 x 15w front facing speakers
- Integrated Mini OPS Slot (Mini OPS units sold separately)
- USB-C front socket
- Mobile and electric height-adjustable options available
- 5 Year on-site warranty
- Ships with wall-mount bracket



# HDI edge 2.0 touchscreen 55"

## TECHNICAL SPECIFICATIONS

|                        |  |
|------------------------|--|
| Resolution             | Up to 3840 x 2160 @ 60Hz   |
| Display Features       | LED backlight  |
| Screen dimension       | 55" / 1209.6mm x 680.4mm   |
| Set dimension          | 50.06" (L) x 31.64" (H) x 3.09" (W) / 1271.6mm (L) x 803.7mm (H) x 78.5mm (W) - Not including base |
| Temperature / Humidity | 0°C ~ 40° / ≤80%   |
| Audio                  | 15W x 15W internal speakers  |
| Aspect Ratio           | 16:9   |
| Brightness             | 500 cd/m2  |
| Contrast               | 1200:1 or higher   |
| Colours                | 10bit, 1.07 Billion colours  |
| View Angle             | 178°   |
| Screen Mode            | 16:9 / 4:3 / dot to dot / Full screen  |
| Support Resolution     | 4K Ultra HD 3840 x 2160 @60Hz  |
| Voltage range          | AC 100-240V~, 50/60Hz  |
| Power range            | Standby Power <1W - Working 230W   |
| VESA mount             | 400 x 400 mm, M8 Screw   |
| Panel Response Time    | 8 ms   |

## CONNECTIVITY

| FRONT            |             | REAR                 |                   |
|------------------|-------------|----------------------|-------------------|
| HDMI             | 1           | <b>SIDE</b>          |                   |
| USB 3.0 A (Blue) | 3           | HDMI                 | 2                 |
| USB 3.0 B (Blue) | 1 x (Touch) | USB 2.0 A (White)    | 1                 |
| USB 3.0 Type C   | 1           | USB 3.0 A (Blue)     | 2                 |
|                  |             | USB 3.0 B (Touch)    | 2                 |
|                  |             | USB 3.0 Type C       | 1                 |
|                  |             | DP                   | 1                 |
|                  |             | HDMI OUT             | 1                 |
|                  |             | <b>BOTTOM</b>        |                   |
|                  |             | VGA                  | 1 x DE-15F        |
|                  |             | VGA Audio (PC) Input | 1 x 3.5 stereo    |
|                  |             | MIC Input            | 1 x 3.5 stereo    |
|                  |             | Headphone Out        | 1 x 3.5           |
|                  |             | Network (LAN)        | 2 x RJ45 IN - OUT |
|                  |             | USB 3.0 B (Touch)    | 1                 |
|                  |             | SPDIF                | 1 RCA             |

## ANDROID 13 SPECIFICATIONS

|                |  |
|----------------|--|
| CPU            | 4 x ARM Cortex-A73 2.28GHz 64 bit<br>4 x ARM Cortex-A53 2.28GHz 64 bit |
| GPU            | 8 x ARM Mali-G52   |
| Dual wifi card | WIFI 6 & 8 Bluetooth + WIFI 5G   |
| SD RAM         | 8GB DDR4   |
| EMMC           | 64G  |

## TOUCH PARAMETERS

|                        |  |
|------------------------|--|
| Touch Technology       | Infrared Touch                               |
| Touch points           | Up to 20 point multi touch                   |
| Writing mode           | Finger, stylus or any non-transparent object |
| Positioning technology | IR technology                                |
| Positioning accuracy   | <1mm   |
| Positioning resolution | 4096 x 4096                                  |
| Response time          | 5ms  |
| Cursor speed           | 180 dot/sec                                  |
| Connection Port        | USB plug and play                            |
| Operating system       | Windows / Linux / Mac / Android              |
| PC response            | System auto response                         |



## MOBILITY

### Solutions

At HDi we pride ourselves on designing and building customised solutions to solve many bespoke problems.

## PHYSICAL SPECIFICATIONS

|                     |  |
|---------------------|--|
| Package Dimensions  | 54.53" (L) x 36.22" (H) x 6.30" (W) / 1385mm (L) x 920mm (H) x 160mm (W) |
| Gross weight in box | 35KG / 77.16lbs  |
| Screen Dimensions   | 1271.6mm (L) x 803.7mm (H) x 78.5mm (W)                                  |
| Net Weight          | 26KG / 57.32lbs  |

### Remark:

Above mentioned parameters are for Standard models and are subject to change without notice. \* Not all applications are compatible with Android 11.

