HDi edge 2.0 touchscreen 65"

Code: HDi-65 EDGE 2.0



4K Resolution



AirServer App



4 mm Toughened glass



Slim IR Technology





HDi edge 2.0 interactive touchscreens build upon HDi's renowned interactive technology to give the ultimate medium for presentations, interaction and collaboration.

Every HDi Edge 2 .0 interactive screen incorporates 20 points of touch, dual Wi-Fi for improved Airserver screen sharing, USB-C ports for single cable connectivity, remote management and access to both the Google Play Store and HDi's own managed app store.



Features





- Powered by HDi OS™ (Built on Android 13)
- 500 nits of Brightness
- Multi-touch Up to 20 touch points
- Super fast response time
- Inbuilt Airserver app for device mirroring
- Pre-installed interactive apps
- 2 x 15w front facing speakers
- Integrated Mini OPS Slot (Mini OPS units sold separately)
- USB-C front socket
- Mobile and electric height-adjustable options available
- 5 Year on-site warranty
- Ships with wall-mount bracket

What is in the box?

- 1 x Magnetic Pen
- 1 x HDMI Cable
- 1 x Touch USB
- 1 x Power IEC Cable



- 1 x Warranty Card
- 1 x Remote

HDi edge 2.0 touchscreen 65"

TECHNICAL SPECIFICATIONS

Resolution Up to 3840 x 2160 @ 60Hz

Display Features LED backlight

Screen dimension 65" / 1428.5mm x 803.5mm

Set dimension 58.14" (L) x 36.13" (H) x 3.45" (W) / 1476.8mm (L) x 917.8mm (H) x 87.7mm (W) - Not including base

Temperature / Humidity 0°C ~ 40° / ≤80%

Audio 15W x 15W internal speakers

Aspect Ratio 16:9
Brightness 500 cd/m2
Contrast 1200:1 or higher
Colours 10bit, 1.07 Billion colours

View Angle 178°

Screen Mode 16:9 / 4:3 / dot to dot / Full screen
Support Resolution 4K Ultra HD 3840 x 2160 @60Hz

Voltage range AC 100-240V~, 50/60Hz

Power range Standby Power <1W - Working 230W

VESA mount 500 x 400 mm, M8 Screw

Panel Response Time 8 ms

CONNECTIVITY

FRONT		
HDMI	1	
USB 3.0 A (Blue)	3	
USB 3.0 B (Blue)	1 x (Touch)	
IISB 3.0 Type C	1	

REAR	
SIDE	
HDMI	2
USB 2.0 A (White)	1
USB 3.0 A (Blue)	2
USB 3.0 B (Touch)	1
USB 3.0 Type C	_1
DP	1
HDMI OUT	1

 BOTTOM

 VGA
 1 x DE-15F

 VGA Audio (PC) Input
 1 x 3.5 stereo

 MIC Input
 1 x 3.5 stereo

 Headphone Out
 1 x 3.5

 Network (LAN)
 2 x RJ45 IN - OUT

 USB 3.0 B (Touch)
 1

1 RCA

ANDROID 13 SPECIFICATIONS

CPU 4 x ARM Cortex-A73 2.28GHz 64 bit 4 x ARM Cortex-A53 2.28GHz 64 bit

GPU 8 x ARM Mali-G52

Dual wifi card WIFI 6 & 8 Bluetooth + WIFI 5G

SD RAM 8GB DDR4 EMMC 64G



TOUCH PARAMETERS

SPDIF

Touch Technology Infared Touch Touch points Up to 20 point multi touch Writing mode Finger, stylus or any non-transparent object Positioning technology IR technology Positioning accuracy <1mm Positioning resolution 4096 x 4096 Response time 5ms Cursor speed 180 dot/sec Connection Port USB plug and play Windows / Linux / Mac / Android Operating system PC response System auto response



MOBILITY

Solutions

At HDi we pride ourselves on designing and building customised solutions to solve many bespoke problems.

PHYSICAL SPECIFICATIONS

 Package Dimensions
 62.80" (L) x 39.76" (H) x 6.30" (W) / 1595mm (L) x 1010mm (H) x 160mm (W)

 Gross weight in box
 43KG / 94.80lbs

 Screen Dimensions
 1476.8mm (L) x 917.8mm (H) x 87.7mm (W)

 Net Weight
 34KG / 74.96lbs

Remark:

Above mentioned parameters are for Standard models and are subject to change without notice. * Not all applications are compatible with Android 11.



